

GLASS BUBBLES

WATERPROOF FILLING & BONDING

Glass Bubbles are hollow glass spheres with a more variable particle size than microballoons. Being composed chemically of glass, they are physically harder than microballoons and filled resin mixes are noticeably more difficult to sand.

However, glass bubbles produce a more waterproof filler mix and are often used on below-waterline applications on boats. Being significantly less expensive than microballoons they are often preferred if easy sanding performance is not of prime importance. They can be mixed with microballoons in any proportion for color purposes.

Gurit has a range of filler powders which are designed to modify the properties of Gurit multi-purpose systems, and so create resin mixes for use as fillers and adhesives. The fillers form three distinct categories: hollow spheres, short fibers, and flow modifiers.

PRODUCT DETAILS

Composition:	'C' Class
Appearance:	White Powder
Particle Size:	40 - 80 microns
Particle Density:	200g/litre approx.
Bulk Density:	100 - 150g/litre approx..



- Hollow glass spheres
- Physically harder and more difficult to sand
- Waterproof or lowest-cost filler for general applications
- Hard surface finish filler for hard wearing edges and surfaces
- Low strength bonding of softwood
- White in color

INSTRUCTIONS FOR USE

Below are approximate filler loadings for making adhesive and filler mixes together with AMPRO multi-purpose systems. For further information please refer to the respective AMPRO datasheet.

ADHESIVE MIXES

All filler additions are approximate and can be adjusted by the user to achieve the desired consistency.

FILLER TYPE	DESCRIPTION	FILLER QUANTITY		AMPRO SILICA ADDITION*		APPROX. DENSITY	APPROX. VOLUME
		%	FOR 1KG	%	FOR 1KG		
Microballoons**	Brown, low density	15 - 20	150 - 200g	3 - 5	30 - 50g	0.7 g/cm ³	1.8 Ltrs
Glass Bubbles**	White, low density	15 - 20	150 - 200g	4 - 6	40 - 60g	0.6 g/cm ³	2.0 Ltr
Microfibres	Opaque, high strength	7 - 10	70 - 100g	2 - 4	20 - 40g	0.9 g/cm ³	1.0 Ltr

*calculated by weight relative to the mixed system of resin and hardener

FILLING AND FAIRING MIXES

All filler additions are approximate and can be adjusted by the user to achieve the desired consistency.

FILLER TYPE	DESCRIPTION	EASE OF SANDING	WATER RESISTANCE	FILLER QUANTITY		AMPRO SILICA ADDITION*		APPROX. DENSITY	APPROX. VOLUME
				%	FOR 1KG	%	FOR 1KG		
Microballoons	Brown, Low Density	Easy	Moderate	25 - 30	250 - 300g	2 - 3	20 - 30g	0.6 g/cm ³	2.2 Ltrs
Glass Bubbles	White, Low Density	Moderate	High	35 - 40	350 - 400g	3 - 5	30 - 50g	0.5 g/cm ³	3.0 Ltrs

*calculated by weight relative to the mixed system of resin and hardener

**Microfibres are always preferred for load-carrying adhesive joints

MIXING & HANDLING

When mixing add Microballons, Glass bubbles or Microfibres first to the mixed resin / hardener and mix in fully. Add the silica next to the stiffness of mix required. Always pay particular attention to the sides and bottom of the mixing vessel, to ensure an even consistency of the entire mix.

AVAILABILITY

The product is available in a number of formats as shown in the table below. Please contact your local customer support representative for more information.

FILLER TYPE	500ML	300G	5KG	NOTE
Glass Bubbles	A230-005	A230-001	A230-003	All quantities are approximate due to the low density nature of the fillers.

TRANSPORT & STORAGE

The product should be kept in securely closed containers during transport and storage. Adequate long term storage conditions will result in a shelf life, as per table, see product container label for expiry date.

COMPONENT	UNITS	10 - 25°C
Glass Bubbles	Months	24

HEALTH AND SAFETY

The following points must be considered:

1. Skin contact must be avoided by wearing protective gloves. Gurit recommends the use of disposable nitrile gloves for most applications. The use of barrier creams is not recommended, but to preserve skin condition a moisturizing cream should be used after washing.
2. Protective clothing should be worn when mixing, laminating or sanding. Contaminated work clothes should be thoroughly cleaned before re-use.
3. Eye protection should be worn if there is a risk of resin, hardener, solvent or dust entering the eyes. If this occurs flush the eye with water for 15 minutes, holding the eyelid open, and seek medical attention.
4. Ensure adequate ventilation in work areas. Respiratory protection should be worn if there is insufficient ventilation. Solvent vapors should not be inhaled as they can cause dizziness, headaches, loss of consciousness and can have long term health effects.
5. If the skin becomes contaminated, then the area must be immediately cleansed. The use of resin-removing cleansers is recommended. To finish, wash with soap and warm water. The use of solvents on the skin to remove resins etc must be avoided.

Washing should be part of routine practice:

- before eating or drinking
- before smoking & vaping
- before using the lavatory
- after finishing work

6. The inhalation of sanding dust should be avoided and if it settles on the skin then it should be washed off. After more extensive sanding operations a shower/bath and hair wash is advised.

Gurit produces a separate full Safety Data Sheet for all hazardous products. Please ensure that you have the correct SDS to hand for the materials you are using before commencing work.

NOTICE

All advice, instruction or recommendation is given in good faith but the selling Gurit entity (the Company) only warrants that advice in writing is given with reasonable skill and care. No further duty or responsibility is accepted by the Company. All advice is given subject to the terms and conditions of sale (the Conditions) which are available on request from the Company or may be viewed at Gurit's Website: www.gurit.com/terms-and-conditions.aspx

The Company strongly recommends that Customers make test panels in the final process conditions and conduct appropriate testing of any goods or materials supplied by the Company prior to final use to ensure that they are suitable for the Customer's planned application. Such testing should include testing under conditions as close as possible to those to which the final component may be subjected. The Company specifically excludes any warranty of fitness for purpose of the goods other than as set out in writing by the Company. Due to the varied nature of end-use applications, the Company does, in particular, not warrant that the test panels in the final process conditions and/or the final component pass any fire standards.

The Company reserves the right to change specifications and prices without notice and Customers should satisfy themselves that information relied on by the Customer is that which is currently published by the Company on its website. Any queries may be addressed to the Technical Services Department.

Gurit is continuously reviewing and updating literature. Please ensure that you have the current version by contacting your sales contact and quoting the revision number in the bottom left-hand corner of this page.

CONTACT INFORMATION

Please see local contact information at www.gurit.com

24-HOUR CHEMICAL EMERGENCY NUMBER

For advice on chemical emergencies, spillages, fires or exposures:

Europe	+44 1273 289451
Americas	+1 646 844 7309
APAC	+65 3158 1412

customer.support@gurit.com

www.gurit.com

All trademarks used or mentioned in this document are protected by law.